Honeywell Titan™ 7686 **Polymers for Asphalt Modification**

Honeywell Titan™ 7686 can be used to modify asphalt for paving applications.

TYPICAL PROPERTIES:

Property	Value
Hardness @ 25°C (77°F)	<0.5 dmm
Drop Point, Mettler	137°C (279°F)
Density	0.99 g/cc
Viscosity @ 150°C (302°F) Brookfield	4,500 cps
Acid Number	25 mg KOH/g

PRODUCT FORM AND PACKAGING:

Property	Value
Product Form	granule
Size	100% minus 5 mesh
Bulk Density	625 kg/m³ (37 lb/ft³)
	1,000 kg Super Sacks Other packaging options may be available

SAFETY PRECAUTIONS:

Honeywell polymers are regarded as non-hazardous when exposure is controlled by using accepted industrial hygiene practices. Consult our Material Safety Data Sheet for specific recommendations on safe handling.

OFFICES:

Honeywell

Corporate Headquarters

101 Columbia Road Morristown NJ, 07962

Tech Assistance: 973-455-5382 Customer Service: 973-455-2145

Toll Free in US:

Tech Assistance: 800-451-9961 Customer Service: 888-245-4738

Europe / Middle East / Africa / India Honeywell Belgium NV

Interleuvenlaan 15i 3001 Heverlee, Belgium Telephone: +32 16 39 12 11 Fax: +32 16 40 00 33

Asia / Pacific Honeywell

No.430, Li Bing Road, Zhangjiang Hi-Tech Zone, Shanghai 201203

China

Telephone: +8621 2894-2000 Fax: +8621 5855-3543

WEBSITE: www.honeywell-titan.com

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

