Hard, high drop point, high density, higher molecular weight (MW), oxidized polyethylene (HDOxPEs) homopolymer in powder form mainly used as a process aid for PVC extrusion. Its low acid number does not allow it be emulsified for use in aqueous systems, like most of Honeywell's other high density oxidized polyethylene (HDOxPEs).

## **TYPICAL PROPERTIES**

Property	Value
Hardness	<0.5
Viscosity @ 140° C	85000
Drop Point, Mettler	140°C (284°F)
Density	0.98
Acid Number	7

## **REGULATORY APPROVALS**

Property	Value
Plastic Pipe Institute/NSF*	Yes
FDA Indirect Approvals*	Yes

## **PRODUCT FORM AND SIZE**

Property	Value
Product Form	Granule

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

@ 2021 Honeywell International Inc.

All rights reserved

