# Honeywell HPL 6910 Ester Lubricant

HPL 6910 is high molecular weight ester lubricant for plastic processing. It will improve the flow of the plastic melt in the die and provide metal release and gloss. It can be used as the main external lubricant or in combination with other lubricants for the extrusion or injection molding parts.

## **Typical Properties:**

Property	Value
Viscosity @ 116°C	50 cSt
Acid Number (ASTM D-1386)	10 mg KOH/g

### Product form and packaging:

Property	Value
Product State	Wax like
Product Form	Free flowing prill or Powder
Package Size	25 kg
Packages Per Pallet	40
Net Weight	1000 kg

### **Safety Precautions**

Consult our Material Safety Data Sheet for specific recommendations on safe handling.

#### For additional information or to contact us, please visit: www.honeywell-additives.com

### Honeywell Corporate

Headquarters 115 Tabor Road Morris Plains, NJ 07950 Tech Assistance: 973-455-5382 Toll Free in U.S.: Tech Assistance: 800-451-9961 Customer Service: 888-245-4738 Asia / Pacific Honeywell No.430, Li Bing Road, Zhangjiang Hi-Tech Zone, Shanghai 201203 China Telephone: +8621 2894-2000 Fax: +8621 5855-3543

### Europe / Middle East /

Africa Honeywell Belgium N.V. Gaston Geenslaan 14 3001 Heverlee Belgium Telephone: +32 16 39 12 11 Fax: +32 16 39 13 71

#### Honeywell International (I) Pvt Ltd

6th Floor, Tower B, Building No.9 DLF Cyber City, Phase III Gurgaon-122002 Haryana India Telephone: +91-124-4031361-65

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2015 Honeywell International Inc. All rights reserved

ISO 9001:2000 Certified

