Typical Alkaline Materials (Bases) for Neutralization of HF

Alkaline Material	Common Names	Form Available	Hazards and Reaction	Lb. / Lb. 100% HF	Salt Properties
Sodium Hydroxide (NaOH)	Caustic Soda	100% Solid Beads or Flake <50% Solution	Dot Class 8 (Crossive) Very High Heat of Dilution & Neutralization*	4.0 lb. / lb. 100% HF	Sodium Fluoride (NaF) DOT Class 6 (Poison) Sol. in Water = 4.0%
Potassium Hydroxide (KOH)	Caustic Potash	85% Solid Beads or Flake <45% Solution	Dot Class 8 (Crossive) Very High Heat of Dilution & Neutralization*	6.23 lb. / lb. 100% HF	Potassium Fluoride (KF) DOT Class 6 (Poison) Sol. in Water >40%
Sodium Carbonate (Na ₂ Co ₃)	Soda Ash	Dry Powder	Rapid Evolution of Carbon Dioxide Gas (CO ₂)	2.85 lb. / lb. 100% HF	Sodium Fluoride (NaF) DOT Class 6 (Poison) Sol. in Water = 4.0%
Sodium Bicarbonate (NaHCO ₃)	Bicarb Baking Soda	Dry Powder	Rapid Evolution of Carbon Dioxide Gas (CO ₂)	4.20 lb. / lb. 100% HF	Sodium Fluoride (NaF) DOT Class 6 (Poison) Sol. in Water = 4.0%
Calcium Carbonate (CaCO ₃)	Limestone	Pebbles	Slow Reaction Slow Evolution of Carbon Dioxide Gas (CO ₂) Pebble Surface Can Become Passivated	2.69 lb. / lb. 100% HF	Calcium Fluoride (CaF ₂) Non-hazardous Sol. In Water = 0.004%
Calcium Oxide (CaO)	Quicklime	Dry Powder	DOT Class 8 (Corrosive) Very High Heat of Hydration & Neutralization*	1.46 lb. / lb. 100% HF	Calcium Fluoride (CaF ₂) Non-hazardous Sol. In Water = 0.004%
Calcium Hydroxide [Ca(OH) ₂]	Hydrated Lime	Dry Powder Slurry in Water	High Heat of Neutralization* Slippery When Wet	2.01 lb. / lb. 100% HF	Calcium Fluoride (CaF ₂) Non-hazardous Sol. In Water = 0.004%

^{*} NOTE: To better control heat of neutralization, the HF spill and neutralizing base should be diluted as much as practical, considering the need to control all effluents.

Honeywell Fluorine Products 101 Columbia Road Morristown, NJ 07962-1053 www.hfacid.com All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated herein, or that other measures may not be required. The values presented herein are typical values and are not to be interpreted as product specifications. User assumes all liability for use of the information and results obtained.

