Honeywell Aclar® Rx160

Effective Date: 12/08/08 **Revised Date: 07/15/10**

Aclar® Rx160 is a 0.60 mil (15 micron) PCTFE homopolymer, high performance barrier film for the pharmaceutical and medical markets. It thermoforms well on conventional blister packaging equipment and offers all the benefits of Aclar® where barrier considerations are less demanding.

Properties of 0.60 mil (15μ) film at 73°F- 50% RH		Typical Value		To all Martin and
		English	Metric	Test Method
Specific Gravity		2.11		ASTM D1505
Yield		21,896 in²/lb.	31.14 m ² /kg	
Haze		< 1 %		ASTM D1003
Crystalline Melting Point		412°F	211°C	ASTM D4591
Dimensional Stability (10 mins. @ 300°F/149°		≤ + 12 % < - 12 %		ASTM D1204
Tensile Strength	- MD - TD	11,000 – 17,000 psi 5,500 – 7,000 psi	76 - 117 MPa 38 - 48 MPa	ASTM D882
Elongation	- MD - TD	80 - 130 % 200 - 275 %		ASTM D882
Modulus, secant	- MD - TD	200,000 - 240,000 psi 180,000 - 220,000 psi	1379 - 1655 MPa 1241 - 1517 MPa	ASTM D882
Surface Tension (treated side)		≥ 42 dynes/cm		ASTM D2578
Water Vapor Transmission Rate @ 77°F (25°C) / 60% RH @ 86°F (30°C) / 60% RH @ 86°F (30°C) / 65% RH @ 104°F (40°C) / 75% RH @ 100°F (37.8°C) /100% RH		gms/100in²/day 0.0033 0.0060 0.0062 0.0210 0.0270	gms/m²/day 0.051 0.093 0.096 0.326 0.419	ASTM F1249

Aclar® is manufactured in accordance with industry accepted standards for cGMP. It complies with the following regulations and requirements: FDA 21 CFR 177.1380, USP Class VI Plastics, and EU Directive 2002/72/EC. Drug Master File #1578 has been established with the FDA for Aclar® Films. Please contact your Honeywell representative for additional information and detailed compliance statements.

Honeywell

Health Care & Packaging 101 Columbia Road Morristown, NJ 07962 Telephone: 973-455-3990 Toll Free: 800-9-FILMS-9 Fax: 973-455-6191

Honeywell (Europe)

Health Care & Packaging Haasrode Research Park B 3001, Heverlee (Leuven) Belgium

Telephone: 32 16 391 211 Fax: 32 16 391 363

NOTICE: All statements, information and data given herein are believed to be accurate and reliable, but are presented without guarantee, warranty or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that measures may not be required. The values presented in this data sheet are typical values and are not to be interpreted as product specifications



