

SOLSTICE[®] 513A (R-513A)

Technical Information

Solstice 513A is a non-ozone depleting, low global warming potential (GWP) hydrofluoro-olefin (HFO)-based refrigerant developed to replace R-134a in positive displacement, direct expansion, medium-temperature commercial and industrial chillers, as well as flooded and/or centrifugal chillers. Solstice 513A is an excellent capacity and efficiency match for R-134a in new systems, as well as for retrofit of existing systems, offering an optimal balance of properties including high energy efficiency and lower GWP, which is better for the environment.



BENEFITS

- Reduced GWP: 56% reduction compared to R-134a
- Excellent capacity and energy efficiency match to R-134a
- Close performance match to R-134a for retrofit and new systems
- Azeotrope with zero glide
- Safe and nonflammable (ASHRAE A1)
- Approved by major equipment and component manufacturers
- Compatible with existing R-134a equipment design/lubricants
- Oil change and seal replacement is necessary when retrofitting systems running on HCFC service blends.

APPLICATIONS

- Medium-temperature circuit of hybrid cascade systems
- Medium-temperature commercial and industrial DX refrigeration
- Water chillers, air conditioning, and heat pumps
- Ice rinks
- New equipment/retrofit of existing systems

SOLSTICE 513A PROPERTIES

ASHRAE Number	R-513A
Composition	R-1234yf
Weight %	56.0/44.0
Molecular Weight	108.4 g/mole (108.4 lb/lb mole)
Boiling Point at 1 atm (101.3 kPa)	-29.2 °C (-20.6 °F)
Critical Pressure	3766 kPa [abs] (546.2 psia)
Critical Temperature	96.5 °C (173.7 °F)
Liquid Density at 21.1 °C (70 °F)	1185.7 kg/m ³ (74.0 lb/ft ³)
Ozone Depletion Potential (CFC-11 = 1.0)	0
AR5 Global Warming Potential	573
ASHRAE Safety Classification	A1
Temperature Glide	0 °R (0 K)



Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Solstice[®] is a registered trademark of Honeywell International Inc.

Honeywell International

115, Tabor Road, Morris Plains
New Jersey, USA

advancedmaterials.honeywell.com

TCS-23-17-EN | 08/23
© 2023 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell